

A revolution for a professional washing way

AQUA Bright[®] RENT

ENVIRONMENTALLY FRIENDLY | LOWER ENERGY COSTS
EXCEPTIONAL DURABILITY



Rental and sale of industrial washing machines and dryers

Discover the advantages :

- Save up to 60% on energy bills
- Electric dryers
- Save time with fast programs up to 45 min (60° C with prewash)
- Drum capacity of 7 kg
- Free !! automatic soap dispenser Aqua Bright

Aqua Bright Rent N.V.
Ferd. Coosemansstraat 150
2600 Berchem - Antwerpen
Tel. +32 3 286 85 77
Fax +32 3 218 45 29

info@aquabright-rent.be
www.aquabright-rent.be

Spirit topLine 8120

- Load capacity 7kg
- Gentle drum
- Drum capacity 66l
- Spin speed 1500rpm
- G factor 613
- Residual moisture 43%
- With drain valve or drain pump
- Language selection
- 50 profiClean programmes
- Door hinge right or left
- Anthracite or chrome steel finish



Spirit topLine washing machines

Company or brand name:	Schulthess
Type of appliance:	Washing machine
Type of sales description:	Spirit topLine 8120
Product no	
Model with drain pump (P):	81201EPU
Model with drain valve (V):	81201EUV

Application features ¹⁾		
Filling amount	max kg	7
Drum volume	l	66
Spin speed	max rpm	1500
G force	g	613
Residual moisture	%	43
Duration cold water connection	min	56
Duration hot water connection	min	45

Consumption data		
Energy consumption		
- cold water connection	kWh	1,29
- hot water connection 70°C	kWh	0,16
Water consumption	l	62

Structural form	
Footed appliance with work surface	•
Door hinge	r/l/i

Dimensions	
Height	cm 90
Width	cm 63
Depth including space from wall	cm 74
Depth with door open (front loader)	cm 114
Height adjustable	cm 2
Empty weight	kg 98

Equipment	
Detergent tank and drum	chrome-nickel steel
Door opening	Ø cm front 30
Automatic door opening	•
Connecting cable	m 1,6
Drain	
- Drain hose with bends only model (P)	m 1,5
- Model with drain pump (P)	Ø mm 22
- Model with drain valve (V)	Ø mm 50

Electric power and water supply	
Electrical connection	V 400 3N-/50Hz/4,4kW/10A
Voltage/connected loads/fuse	
	V 400 2N-/50Hz/4,4kW/10A
	V 230 1N-/50Hz/2,1kW/10A
	V 230 1N-/50Hz/2,5kW/13A
	V 230 3-/50Hz/4,4kW/13A

Water connection	
- Pressure hose G ¾" with fine filter	m 1,5
- Can be connected to cold water/hot water:	cold water/hot water 70°C
- Water pressure	bar 0,1-1MPa (1-10bar)

Options	
- Execution in chrome steel	
- Door hinge left	
- Drain valve or drain pump	
- Programme expansion module with PC interface	
- Load sensor with weight detection	
- Connection for liquid detergent pumps	
- Cash card system	
- Machine plinth in chrome steel (305mm)	

Safety and service	
Complies with Swiss safety regulations SEV-tested	
Complies with the European Machinery Directive 2006/42/EC	

Spirit topLine TA 8320

- Load capacity 7kg
- Stainless steel drum
- Drum capacity 153l
- Exhaust air system
- Electronically and time-controlled drying programmes
- Residual moisture measuring system
- Drying capacity 11,5kg/hour
- Language selection
- Door hinge right or left
- Anthracite or chrome steel finish



Spirit topLine TC 8330

- Load capacity 7kg
- Stainless steel drum
- Drum capacity 153l
- Condensation system
- Electronically and time-controlled drying programmes
- Residual moisture measuring system
- Drying capacity 9kg/hour
- Language selection
- Door hinge right or left
- Anthracite or chrome steel finish



Explications

- no • yes

1) Values determined in accordance with standard EN 60456 in the standard programme for cotton 60°C without prewash

2) 100% drainage means that after spinning is completed 1kg laundry (dry weight) contains 1 kg of water. The lower the percentage, the less moisture the laundry contains.

This is important for the energy consumption of a dryer.

3) Door hinge l=left, r=right, i=interchangeable. Example: l/l is state as delivered, door hinge left. Hinge interchangeable.

Spirit topLine dryers

Company or brand name:	Schulthess	Schulthess
Type of appliance:	Exhaust air dryer	Condensation dryer
Type of sales description:	Spirit topLine TA8320	Spirit topLine TC 8330
Product no	8320 1U	8330 1U

Application features

Filling amount		
- Cotton, cupboard	max kg	7
- Cotton, ironing moist	max kg	7
- Easy-care, cupboard dry	max kg	3,5
Drying time		
Programme 'coton, cupboard dry' (laundry spun before beginning drying at about 1500rpm, 43% residual moisture)	min	36
		46

Consumption

Energy consumption		
Programme 'coton, cupboard dry' (laundry spun before beginning drying at about 1500rpm, 43% residual moisture)	kWh	3,0
		2,9

Structural form

Footed appliance with work surface		•
Standard unit for wash and dry column		•
Door hinge	r/l/i	r/l/i

Dimensions¹⁾

Height	cm	90	90
Width	cm	63	63
Depth including space from wall	cm	84	88
Depth with door open	cm	145	149
Height adjustable	cm	2	2
Empty weight	kg	76	86

Control of drying

By time setting		•
Automatic by electronic moisture sensing		•

System and Equipment

Air extraction system		•
Air condensation system		-
Exhaust air duct	Ø 100mm, 90°-angle adapter	-
Exhaust air hose Ø 100	m	2
Drying programs		12
Additional programs and times programs		•
Special programs		10
Mixed		•
Display of te program time		•
Door opening		•
Loading opening	cm front, Ø 36/31	front, Ø 36/31
Connecting cable	m	1,5
Outlet hose	m	-
		2, Ø 22mm
Condensate drain with pump		-
		•

Electric power and water supply

Electrical connection	V	400 3N-/50Hz/5,9kW/10A	400 3N-/50Hz/5,1kW/10A
Voltage/connected loads/fuse	V	400 2N-/50Hz/4,4kW/10A	400 2N-/50Hz/3,7kW/10A
	V	230 1N-/50Hz/2,2kW/10A	230 1N-/50Hz/2,3kW/10A
	V	230 1N-/50Hz/3,7kW/16A	230 1N-/50Hz/3,7kW/16A
	V	230 3-/50Hz/5,9kW/16A	230 3-/50Hz/5,1kW/16A

Options

	- Execution in chrome steel	- Execution in chrome steel
	- Cash card system	- Cash card system
	- Tower kit for washer/dryer column	- Tower kit for washer/dryer column
	- Machine plinth in chrome steel (305mm)	- Machine plinth in chrome steel (305mm)

Safety and service

Complies with Swiss safety regulations	SEV-tested	SEV-tested
Complies with the European Machinery Directive	2006/42/EC	2006/42/EC
Guarantee	1 year	
Service provided by	Schulthess Maschinen AG	
Manufacturer's name and address	Schulthess Maschinen AG, CH-8633 Wolfhausen/ZH	
Country of origin	Switzerland	

Explications

- no • yes
- 1) Values determined in accordance with standard EN 61121
- 2) Door hinge l=left, r=right, i=interchangeable.
Example: l/l is state as delivered, door hinge left. Hinge interchangeable.
- 3) In the case of an exhaust air connection at the rear, a greater distance from the wall may be required. Dimensions are to be found in the dimensioned drawings.
- 4) Set the degree of drying according to the laundry items in accordance with operating instructions.
- 5) Degree of drying maintained automatically.



Your direct benefits :

- Up to 60% energy saving
- Bigger capacity = less labor costs + less energy
- Short programs (35 min at 60°C)
- Better washing results
- A full maintenance contract
- No unexpected invoices
- A fixed monthly deductible cost
- Every 5 years new machines
- At every turn an adjusted and economical addition of soap and softener
- A spotless washing machine and laundry room

Sale and rental of professional washing machines and dryers



Aqua Bright Rent N.V.
Ferd. Coosemansstraat 150
2600 Berchem - Antwerpen
BTW BE 0478.150.117
Tel. +32 3 286 85 77
Fax +32 3 218 45 29
info@aquabright-rent.be
www.aquabright-rent.be

LET US DO YOUR DIRTY WORK